



Job Name:

Job No:

JWC Representative:

Tag No.:

Submitted By:

Date:

Engineer:

Approved By:

Date:

Contractor:

Order No.:

Date:

JPSG Series

Sight Glass Assembly For Liquid Level Verification Standard Bronze Shutoff Valves



SPECIFICATIONS

- Working pressure: 125 PSI @ 350° F, 300 PSI @ 150° F
- Service ratings are subject to the pressure / temperature ratings of the gauge glass and gaskets. Regular glass is used in the standard assembly unless otherwise noted as "red line" or high pressure.
- Shutoff valves: Bronze with Aluminum wheel
- Connection size: ½" NPT
- Gaskets: EPDM
- Equipped with two copper guard rods
- Standard ¼" needle drain valve in lower arm
- CRN Registered

MODEL NUMBER	GLASS O.D.	GLASS LENGTH	CONN SIZE	SHIPPING WEIGHT
	IN	IN	IN	LBS
JPSG-63-008	⅝	8	½	5
JPSG-63-010	⅝	10	½	5
JPSG-63-012	⅝	12	½	5
JPSG-63-016	⅝	16	½	5
JPSG-63-020	⅝	20	½	5

MODEL NUMBER	GLASS O.D.	GLASS LENGTH	CONN SIZE	SHIPPING WEIGHT
	IN	IN	IN	LBS
JPSG-63-022	⅝	22	½	5
JPSG-63-024	⅝	24	½	5
JPSG-63-028	⅝	28	½	5
JPSG-63-030	⅝	30	½	5
JPSG-63-036	⅝	36	½	5

Dimensions are subject to change.
Shipping weights are approximate.