

Job Name:		
Job No:	JWC Representative:	
Tag No.:	Submitted By:	Date:
Engineer:	Approved By:	Date:
Contractor:	Order No.:	Date:

JPSG Series

Sight Glass Assembly For Liquid Level Verification Standard Bronze Shutoff Valves



SPECIFICATIONS

- Working pressure: 125 PSI @ 350° F, 300 PSI @ 150° F
- Service ratings are subject to the pressure / temperature ratings of the gauge glass and gaskets. Regular glass is used in the standard assembly unless otherwise noted as "red line" or high pressure.
- Shutoff valves: Bronze with Aluminum wheel
- Connection size: ½" NPT
- Gaskets: EPDM
- Equipped with two copper guard rods
- Standard ¼" needle drain valve in lower arm
- CRN Registered

MODEL NUMBER	GLASS O.D.	GLASS LENGTH	CONN SIZE	WEIGHT
	IN	IN	IN	LBS
JPSG-63-008	5/8	6 3/4"	1/2	5
JPSG-63-010	5/8	8 3/4"	1/2	5
JPSG-63-012	5/8	10 3/4"	1/2	5
JPSG-63-016	5/8	14 3/4"	1/2	5
JPSG-63-020	5/8	18 3/4"	1/2	5

MODEL NUMBER	GLASS O.D.	GLASS LENGTH	CONN SIZE	WEIGHT
	IN	IN	IN	LBS
JPSG-63-022	5/8	20 3/4"	1/2	5
JPSG-63-024	5/8	22 3/4"	1/2	5
JPSG-63-028	5/8	26 3/4"	1/2	5
JPSG-63-030	5/8	28 3/4"	1/2	5
JPSG-63-036	5/8	34 3/4"	1/2	5

Dimensions are subject to change
Weights are approximate